


Fully slotted Double section - 82x41

The product code F0DC43000 is a sendzimir galvanised, hot-dip galvanised and stainless steel profile bar. It belongs to the category of double profiles and its description is ZF Fully slotted Double section 82X41 MT 3. This product is designed to offer a robust and durable solution for a wide range of industrial and commercial applications. The dimensions are length 3000 mm, width 41 mm, height 82 mm, available in material thicknesses 1.5-2.0-2.5 mm. The product complies with current safety and quality regulations, ensuring reliable and safe use over time. The C-profile shape, double slotted on 3 sides, makes this steel profile bar suitable for use in support structures and mounting systems. Its ease of installation and maintenance is a further advantage, allowing optimisation of operating time and costs. An excellent choice for anyone looking for a reliable solution in the field of profile bars.



F0 DC4 3000

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461

Technical Characteristics	
Dimension	
L	3000
Weight	
[Kg/m]	3,00 - 4,00 - 5,00
*Thickness identifier [mm]	
15 - 20 - 25	1,50 - 2,00 - 2,50

Code composition :

Add the desired coating and thickness to the code.


On demand: L.4000 - 6000

Dimension of slots: 13 x 22

Material: S 235JR - DIN EN 10025 S 250GD -
DIN EN 10326

Fully slotted Double section - 82x41

The product code F0DC43000 is a sendzimir galvanised, hot-dip galvanised and stainless steel profile bar. It belongs to the category of double profiles and its description is ZF Fully slotted Double section 82X41 MT 3. This product is designed to offer a robust and durable solution for a wide range of industrial and commercial applications. The dimensions are length 3000 mm, width 41 mm, height 82 mm, available in material thicknesses 1.5-2.0-2.5 mm. The product complies with current safety and quality regulations, ensuring reliable and safe use over time. The C-profile shape, double slotted on 3 sides, makes this steel profile bar suitable for use in support structures and mounting systems. Its ease of installation and maintenance is a further advantage, allowing optimisation of operating time and costs. An excellent choice for anyone looking for a reliable solution in the field of profile bars.



F0 DC4 3000

Coatings

- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics	
Dimension	
L	3000
Weight	
[Kg/m]	4,00
*Thickness identifier [mm]	
15 - 20 - 25	2,00

Code composition :

Add the desired coating and thickness to the code.


On demand: L.4000 - 6000

Dimension of slots: 13 x 22

Material: S 235JR - DIN EN 10025 S 250GD -
DIN EN 10326

Fully slotted Double section - 82x41

The product code F0DC43000 is a sendzimir galvanised, hot-dip galvanised and stainless steel profile bar. It belongs to the category of double profiles and its description is ZF Fully slotted Double section 82X41 MT 3. This product is designed to offer a robust and durable solution for a wide range of industrial and commercial applications. The dimensions are length 3000 mm, width 41 mm, height 82 mm, available in material thicknesses 1.5-2.0-2.5 mm. The product complies with current safety and quality regulations, ensuring reliable and safe use over time. The C-profile shape, double slotted on 3 sides, makes this steel profile bar suitable for use in support structures and mounting systems. Its ease of installation and maintenance is a further advantage, allowing optimisation of operating time and costs. An excellent choice for anyone looking for a reliable solution in the field of profile bars.



F0 DC4 3000

Coatings

76 ZnMg ZM310 - UNI EN 10346

Technical Characteristics	
Dimension	
L	3000
Weight	
[Kg/m]	3,00 - 4,00 - 5,00
*Thickness identifier [mm]	
15 - 20 - 25	1,50 - 2,00 - 2,50

Code composition :

Add the desired coating and thickness to the code.

On demand: L.4000 - 6000

Dimension of slots: 13 x 22

Material: S 235JR - DIN EN 10025 S 250GD -
DIN EN 10326