



Perforated cable tray



Available in heights (H):

15

Dimension							Thickness Th (18-42)	Weight (01)	Weigh (18-42)	Length	Code	
W (B)	01	03	17	18	41	42	[mm]	[mm]	[Kg/m]	[Kg/m]	[mm]	
50	01	03	17	18	41	42	1,50	2,00	0,81	0,36	2000	NA 002 0105
75	01	03	17	18	41	42	1,50	2,00	1,06	0,48	2000	NA 002 0107
100	01	03	17	18	41	42	1,50	2,00	1,32	0,59	2000	NA 002 0110
125	01	03	17	18	41	42	1,50	2,00	1,57	0,71	2000	NA 002 0112
150	01	03	17	18	41	42	1,50	2,00	1,83	0,82	2000	NA 002 0115
200	01	03	17	18	41	42	1,50	2,00	2,34	1,06	2000	NA 002 0120
250	01	03	17	18	41	42	1,50	2,00	2,85	1,29	2000	NA 002 0125
300	01	03	17	18	41	42	1,50	2,00	3,36	1,52	2000	NA 002 0130
400	01	03	17	18	41	42	1,50	2,00	4,38	1,98	2000	NA 002 0140

List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Send Galvanizing + White Ral 9010
- Aluminium + White Ral 9010
- Stainless steel AISI 316L - UNI EN 10088
- ENAW 1050H24 - Aluminium