



Cable ladder



Available in heights (H):

45

Dimension	Technical Info				Coatings 25-03-41	Coating 25	Coating 42		Code
W (B)	L [mm]	Thickness [mm]	Weigh [Kg/m]	Thickness [mm]	Weigh [Kg/m]				
150	3000	1,50	1,95	2,00	0,87			NT 003 0415	
200	3000	1,50	2,08	2,00	0,93			NT 003 0420	
250	3000	1,50	2,21	2,00	0,98			NT 003 0425	
300	3000	1,50	2,33	2,00	1,04			NT 003 0430	
350	3000	1,50	2,46	2,00	1,09			NT 003 0435	
400	3000	1,50	2,58	2,00	1,15			NT 003 0440	
450	3000	1,50	2,71	2,00	1,21			NT 003 0445	
500	3000	1,50	2,83	2,00	1,26			NT 003 0450	
550	3000	1,50	2,96	2,00	1,32			NT 003 0455	
600	3000	1,50	3,09	2,00	1,38			NT 003 0460	

List of Coatings

- Hot dip galvanizing - UNI EN ISO 1461
- Electro galvanization - DIN 50962
- Stainless steel AISI 316L - UNI EN 10088
- ENAW 1050H24 - Aluminium

Cable ladder

Assembly

