

Separator with bent top edge H: 50 - 75 - 100 - 125

Product code T00340010 is a separator designed with a safety profile and upper edging, which increases its rigidity and safety during installation, even with reduced thicknesses. Installation is carried out directly on site, at the installer's discretion, according to the requirements of the system. The standard length is 2920 mm, with a thickness of 0.8 mm and a height of 100 mm. The separator is made of Sendzimir galvanised steel, but is also available in stainless steel and with a hot-dip galvanised finish. Identified with the description STANDARD SEPARATOR H.100, it is certified according to the safety and quality standards required for installations, ensuring reliability and durability over time.

T0 034 0010

Length: 2920

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 40 Stainless steel AISI 304 - UNI EN 10088



Technical Characteristics	
Dimension	
Cable tray	100
Basket tray	100
Cable ladder	120
H Separator	
H	100
Technical Info	
a	95
w (b)	25
L	2920
Thickness	
[mm]	0,80
Weight	
[Kg/m]	0,76

Certified System
- IMQ - EN 61537-1 ed.2007 - EN 50085-1:2005 ed EN 50085-2-1:2006 - UL file E471266 Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Certifications



Separator with bent top edge H: 50 - 75 - 100 - 125

H 100

Assembly

To be used: **T0 620** - *Not included*