


30° flat elbow with Cover



Available in heights (H):

- 50
- 75
- 100

Dimension							Weight	Technical Info			Code
W (B)	01	03	11	15	40	41	[Kg]	a	w (b)	R	
50	01	03	11	15	40	41	0,25	131	77	100	T0 089 0505
100	01	03	11	15	40	41	0,37	156	127	100	T0 089 0510
150	01	03	11	15	40	41	0,52	181	177	100	T0 089 0515
200	01	03	11	15	40	41	0,68	206	227	100	T0 089 0520
300	01	03	11	15	40	41	1,06	256	327	100	T0 089 0530
400	01	03	11	15	40	41	1,52	306	427	100	T0 089 0540
500	01	03	11	15	40	41	2,05	356	527	100	T0 089 0550
600	01	03	11	15	40	41	2,67	406	627	100	T0 089 0560

Thickness

- T1 089 - Component - 1,00mm
- T1 090 - Cover - 0,80mm

*T0 089 0507 - Dimension on demand

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark