


45° Inside Elbow with Cover

The product with code T00930520, called 45° Inside Elbow with Cover 50x200, is a component for cable routing. The 45° geometry allows the cable route to transition from the horizontal to the vertical plane, maintaining the continuity of the channel and complying with the minimum bending radius. The entire range has an internal radius of 100 mm, in accordance with the installation requirements for electrical and structured cabling systems. The body of the bend is made of 1.0 mm thick Sendzimir galvanised steel, while the cover is 0.8 mm thick. The closure system features a self-locking snap-on cover, designed to ensure quick installation and operational safety thanks to its accident prevention profile. The component is also available in hot-dip galvanised, painted and stainless steel finishes to suit specific requirements in terms of mechanical strength, corrosion and installation environment.



T0 093 0520

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics

Dimension

W (B) 200

Weight

[Kg] 0,56

Technical Info

a 101

w (b) 157

R 100

Certified System

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Certifications



Thickness

T1 093 - Component - 1,00mm

T1 094 - Cover - 0,80mm

***T0 093 0507 - Dimension on demand**