90° Outside Elbow with Cover

Product T00971060, called 90° Outside Elbow with Cover 100x600, is a component designed for cable ducting systems. Its 90° geometry allows the transition from a horizontal to a vertical path, which is particularly useful when the route requires a downward bend, ensuring the continuity of the channel and compliance with the minimum bending radius. The entire range has an internal radius of 100 mm, in accordance with typical requirements of electrical installations and structured cabling systems. The body of the bend is made of Sendzimir galvanized steel with a thickness of 1.0 mm, while the cover has a thickness of 0.8 mm. The closure system features a self-locking snap-on cover, designed to ensure quick installation and operational safety thanks to its accident prevention profile. The component is also available in hot-dip galvanised, painted and stainless steel finishes to suit different requirements for mechanical strength, corrosion protection and environmental conditions of installation.



T0 097 1060

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics	
Dimension	
W (B)	600
Weight	
[Kg]	3,15
Technical Info	
a	230
R	100

Certified System
- IMQ - EN 61537-1 ed.2007 - EN 50085-1:2005 ed EN 50085-2-1:2006 - UL file E471266 Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Thickness

T1 097 - Component - 1,00mm
T1 098 - Cover - 0,80mm

****T0 097 0507 - Dimension on demand***

Certifications

E471266

Zamet S.p.A.
Via Torino, 109 - 10088 Volpiano (TO) - Italy
Tel. +39(011)98.22.601 - www.zamet.it