


## Horizontal "T" Junction with Cover



Available in heights (H):

- 50
- 75
- 100

Dimension	Weight	Technical Info	Code
W (B)	[Kg]	a w (b) R	
50	0,82	180 310 100	T0 105 0505
100	1,23	230 360 100	T0 105 0510
150	1,71	280 410 100	T0 105 0515
200	2,26	330 460 100	T0 105 0520
300	3,57	430 560 100	T0 105 0530
400	5,17	530 660 100	T0 105 0540
500	7,05	630 760 100	T0 105 0550
600	9,20	730 860 100	T0 105 0560

### Thickness

- T1 105 - Component - 1,00mm
- T1 106 - Cover - 0,80mm

### \*T0 105 0507 - Dimension on demand

#### Certifications



#### List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

#### Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark