


“T” junction descending with Cover



Available in heights (H):

- 50
- 75
- 100

Dimension	Weight	Technical Info	Code
W (B)	[Kg]	a w (b) R	
50	0,85	180 311 100	T0 113 0505
100	1,12	180 311 100	T0 113 0510
150	1,38	180 311 100	T0 113 0515
200	1,65	180 311 100	T0 113 0520
300	2,19	180 311 100	T0 113 0530
400	2,72	180 311 100	T0 113 0540
500	3,26	180 311 100	T0 113 0550
600	3,79	180 311 100	T0 113 0560

Thickness

- T1 113 - Component - 1,00mm
- T1 114 - Cover - 0,80mm

***T0 113 0507 - Dimension on demand**

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark