


“T” Junction rising with Cover

Product T01151060, known as the 100x600 upward-facing T-joint with cover, is a t-shaped component designed to connect three sections of ducting arranged on two different levels, ensuring a neat and safe cable route that complies with current electrical installation regulations.

It is particularly suitable for domestic and industrial electrical installations requiring a high degree of flexibility in cable routing. The entire range is manufactured with an internal radius of 100 mm, in line with the requirements of modern electrical installations and structured cabling infrastructure.

The body of the connector is made of 1.0 mm thick Sendzimir galvanised steel, whilst the cover, fitted with a self-locking snap-fit closure system, is made of 0.8 mm thick material. This system ensures rapid installation, high operational safety and effective protection thanks to its safety profile.

The product is also available in hot-dip galvanised, painted and stainless steel versions to meet different requirements in terms of mechanical strength, corrosion protection and suitability for specific environmental installation conditions.



T0 115 1060

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics	
Dimension	
W (B)	600
Weight	
[Kg]	4,52
Technical Info	
a	230
w (b)	361
R	100

Certified System
- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Thickness

T1 115 - Component - 1,00mm

T1 092 - Cover - 0,80mm

***T0 115 0507 - Dimension on demand**

Certifications

