


Descending skewed "T" junction with Cover



Available in heights (H):

50

75

100

Dimension	Weight	Technical Info	Code
W (B)	[Kg]	a w (b) R	
50	0,90	200 310 100	T0 117 0505
100	1,50	250 360 100	T0 117 0510
150	2,25	300 410 100	T0 117 0515
200	3,15	350 460 100	T0 117 0520
300	5,43	450 560 100	T0 117 0530
400	8,32	550 660 100	T0 117 0540
500	11,83	650 760 100	T0 117 0550
600	15,96	750 860 100	T0 117 0560

Thickness

T1 117 - Component - 1,00mm

T1 118 / T1 128 - Covers - 0,80mm

*T0 117 0507 - Dimension on demand

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark