


Rising skewed "T" junction with Cover



Available in heights (H):

50

75

100

Dimension	Weight	Technical Info	Code
W (B)	[Kg]	a w (b) R	
100	1,65	250 360 100	T0 119 1010
150	2,43	300 410 100	T0 119 1015
200	3,36	350 460 100	T0 119 1020
300	5,73	450 560 100	T0 119 1030
400	8,74	550 660 100	T0 119 1040
500	12,40	650 760 100	T0 119 1050
600	16,87	750 860 100	T0 119 1060

Thickness

T1 119 - Component - 1,00mm

T1 119 / T1 128 - Covers - 0,80mm

*T0 119 0507 - Dimension on demand

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark