



Rising skewed "T" junction with Cover



Available in heights (H):

50

75

100

Dimension							Weight	Technical Info				Code
W (B)							[Kg]	a	w (b)	R		
50	01	03	11	15	40	41	0,90	200	310	100	T0 119 0505	
100	01	03	11	15	40	41	1,54	250	360	100	T0 119 0510	
150	01	03	11	15	40	41	2,33	300	410	100	T0 119 0515	
200	01	03	11	15	40	41	3,30	350	460	100	T0 119 0520	
300	01	03	11	15	40	41	5,70	450	560	100	T0 119 0530	
400	01	03	11	15	40	41	8,61	550	660	100	T0 119 0540	
500	01	03	11	15	40	41	12,28	650	760	100	T0 119 0550	
600	01	03	11	15	40	41	16,60	750	860	100	T0 119 0560	

Thickness

T1 119 - Component - 1,00mm

T1 119 / T1 128 - Covers - 0,80mm

*T0 119 0507 - Dimension on demand

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark