


Inside "U" joint



Available in heights (H):

- 50
- 75
- 100

Dimension					Weight	Technical Info			Code	
W (B)	01	03	11	15	40	[Kg]	a	w (b)	L	
50	01	03	11	15	40	0,08	45	47	52	T0 203 0505
100	01	03	11	15	40	0,11	45	97	52	T0 203 0510
150	01	03	11	15	40	0,15	45	147	52	T0 203 0515
200	01	03	11	15	40	0,18	45	197	52	T0 203 0520
300	01	03	11	15	40	0,24	45	296	52	T0 203 0530
400	01	03	11	15	40	0,30	45	396	52	T0 203 0540
500	01	03	11	15	40	0,36	45	496	52	T0 203 0550
600	01	03	11	15	40	0,42	45	596	52	T0 203 0560

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088

Certified System


- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Inside "U" joint

Assembly

H50		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
H75-100		n. 8 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 8 M6	T0 621 0600

Not included



In the case of the installation of internal "U" joints on painted items, preparation with equipotential plates is required.