


Flange for reducer for panel mount



Available in heights (H):

50

75

100

Dimension					Thickness	Weight	Technical Info				Code	
W (B)					[mm]	[Kg]	a	w (b)	c	d		
50	01	03	11	15	40	1,50	0,07	75	100	75	50	T0 261 0505
100	01	03	11	15	40	1,50	0,09	75	150	125	50	T0 261 0510
150	01	03	11	15	40	1,50	0,11	75	200	175	50	T0 261 0515
200	01	03	11	15	40	1,50	0,13	75	250	225	50	T0 261 0520
300	01	03	11	15	40	1,50	0,17	75	350	325	50	T0 261 0530
400	01	03	11	15	40	1,50	0,21	75	450	425	50	T0 261 0540
500	01	03	11	15	40	1,50	0,25	75	550	525	50	T0 261 0550
600	01	03	11	15	40	1,50	0,29	75	650	625	50	T0 261 0560

Certifications



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Flange for reducer for panel mount

Assembly

H 50		n. 2 M6x10 / M6x12	TO 620 0610 / TO 620 0612
		n. 2 M6	TO 621 0600
for each flange			
H 75- 100		n. 4 M6x10 / M6x12	TO 620 0610 / TO 620 0612
		n. 4 M6	TO 621 0600
for each flange			

Not included

