


## 90° Inside Elbow without Cover



Available in heights (H):

50

75

100

Dimension							Weight	Technical Info			Code
W (B)							[Kg]	a	R		
50	01	03	11	15	40	41	0,39	180	100	T1 091 0505	
100	01	03	11	15	40	41	0,50	180	100	T1 091 0510	
150	01	03	11	15	40	41	0,62	180	100	T1 091 0515	
200	01	03	11	15	40	41	0,73	180	100	T1 091 0520	
300	01	03	11	15	40	41	0,96	180	100	T1 091 0530	
400	01	03	11	15	40	41	1,19	180	100	T1 091 0540	
500	01	03	11	15	40	41	1,42	180	100	T1 091 0550	
600	01	03	11	15	40	41	1,65	180	100	T1 091 0560	

**Thickness**

Component - 1,00mm

## Certifications



E471266



## List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

## Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark