


Horizontal "T" Junction without Cover



Available in heights (H):

- 50
- 75
- 100

Dimension							Weight	Technical Info			Code
W (B)	01	03	11	15	40	41	[Kg]	a	w (b)	R	
50	01	03	11	15	40	41	0,60	180	310	100	T1 105 0505
100	01	03	11	15	40	41	0,84	230	360	100	T1 105 0510
150	01	03	11	15	40	41	1,11	280	410	100	T1 105 0515
200	01	03	11	15	40	41	1,43	330	460	100	T1 105 0520
300	01	03	11	15	40	41	2,17	430	560	100	T1 105 0530
400	01	03	11	15	40	41	3,07	530	660	100	T1 105 0540
500	01	03	11	15	40	41	4,13	630	760	100	T1 105 0550
600	01	03	11	15	40	41	5,35	730	860	100	T1 105 0560

Thickness

Component - 1,00mm

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark