


“T” side outlet without Cover



Available in heights (H):

- 50
- 75
- 100

Dimension							Weight	Technical Info			Code
W (B)	01	03	11	15	40	41	[Kg]	a	w (b)	R	
75	01	03	11	15	40	41	0,53	160	335	100	T1 109 0707
100	01	03	11	15	40	41	0,56	160	360	100	T1 109 0710
150	01	03	11	15	40	41	0,63	160	410	100	T1 109 0715
200	01	03	11	15	40	41	0,69	160	460	100	T1 109 0720
300	01	03	11	15	40	41	0,81	160	560	100	T1 109 0730
400	01	03	11	15	40	41	0,94	160	660	100	T1 109 0740
500	01	03	11	15	40	41	1,07	160	760	100	T1 109 0750
600	01	03	11	15	40	41	1,19	160	860	100	T1 109 0760

**Thickness**

Component - 1,00mm

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark