

Cover "T" junction descending



Available in heights (H):

50

75

100

Dimension							Thickness	Weight	Code
W (B)							[mm]	[Kg]	
100	01	03	11	15	40	41	0,80	0,28	T1 114 1010
150	01	03	11	15	40	41	0,80	0,40	T1 114 1015
200	01	03	11	15	40	41	0,80	0,51	T1 114 1020
300	01	03	11	15	40	41	0,80	0,74	T1 114 1030
400	01	03	11	15	40	41	0,80	0,96	T1 114 1040
500	01	03	11	15	40	41	0,80	1,19	T1 114 1050
600	01	03	11	15	40	41	0,80	1,42	T1 114 1060

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark