

Cover "T" junction descending



Available in heights (H):

50

75

100

Dimension							Thickness	Weight	Code
W (B)	01	03	11	15	40	41	[mm]	[Kg]	
50	01	03	11	15	40	41	0,80	0,15	T1 114 0505
100	01	03	11	15	40	41	0,80	0,24	T1 114 0510
150	01	03	11	15	40	41	0,80	0,34	T1 114 0515
200	01	03	11	15	40	41	0,80	0,44	T1 114 0520
300	01	03	11	15	40	41	0,80	0,64	T1 114 0530
400	01	03	11	15	40	41	0,80	0,83	T1 114 0540
500	01	03	11	15	40	41	0,80	1,03	T1 114 0550
600	01	03	11	15	40	41	0,80	1,22	T1 114 0560

Certifications



List of Coatings

 Galvanization (Sendzimir method) - UNI EN 10346

 Hot dip galvanizing - UNI EN ISO 1461

 Grey RAL 7032 - ISO9227-ISO6270-ISO2810

 Blue RAL 5015 - ISO9227-ISO6270-ISO2810

 Stainless steel AISI 304 - UNI EN 10088

 Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark