

### Cover "T" junction descending



Available in heights (H):

- 50
- 75
- 100

Dimension							Thickness	Weight	Code
W (B)							[mm]	[Kg]	
75	01	03	11	15	40	41	0,80	0,21	T1 114 0707
100	01	03	11	15	40	41	0,80	0,26	T1 114 0710
150	01	03	11	15	40	41	0,80	0,37	T1 114 0715
200	01	03	11	15	40	41	0,80	0,48	T1 114 0720
300	01	03	11	15	40	41	0,80	0,69	T1 114 0730
400	01	03	11	15	40	41	0,80	0,90	T1 114 0740
500	01	03	11	15	40	41	0,80	1,11	T1 114 0750
600	01	03	11	15	40	41	0,80	1,32	T1 114 0760

#### Certifications



#### List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

#### Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark