



“T” junction rising without Cover



Available in heights (H):

- 50
- 75
- 100

Dimension							Weight	Technical Info			Code	
W (B)							[Kg]	a	w (b)	R		
100	01	03	11	15	40	41	1,41	230	361	100	T1 115	1010
150	01	03	11	15	40	41	1,63	230	361	100	T1 115	1015
200	01	03	11	15	40	41	1,86	230	361	100	T1 115	1020
300	01	03	11	15	40	41	2,31	230	361	100	T1 115	1030
400	01	03	11	15	40	41	2,76	230	361	100	T1 115	1040
500	01	03	11	15	40	41	3,22	230	361	100	T1 115	1050
600	01	03	11	15	40	41	3,67	230	361	100	T1 115	1060

**Thickness**

Component - 1,00mm

Certifications



E471266



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark