


Descending skewed "T" junction with Cover



Available in heights (H):

50

75

100

Dimension							Technical Info				Code	
W (B)							a	w (b)	R	[Kg]		
50	01	03	11	15	40	41	200	310	100	0,65	T1 117 0505	
100	01	03	11	15	40	41	250	360	100	0,99	T1 117 0510	
150	01	03	11	15	40	41	300	410	100	1,41	T1 117 0515	
200	01	03	11	15	40	41	350	460	100	1,91	T1 117 0520	
300	01	03	11	15	40	41	450	560	100	3,14	T1 117 0530	
400	01	03	11	15	40	41	550	660	100	4,68	T1 117 0540	
500	01	03	11	15	40	41	650	760	100	6,54	T1 117 0550	
600	01	03	11	15	40	41	750	860	100	8,71	T1 117 0560	

Thickness

Component - 1,00mm

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark