


Descending skewed "T" junction with Cover



Available in heights (H):

50

75

100

Dimension	Technical Info						Code							
W (B)	a	w (b)	R	[Kg]	T1	117	0707	0710	0715	0720	0730	0740	0750	0760
75	225	335	100	0,90	T1	117	0707							
100	250	360	100	1,09	T1	117	0710							
150	300	410	100	1,50	T1	117	0715							
200	350	460	100	2,00	T1	117	0720							
300	450	560	100	3,23	T1	117	0730							
400	550	660	100	4,78	T1	117	0740							
500	650	760	100	6,64	T1	117	0750							
600	750	860	100	8,81	T1	117	0760							

Thickness

Component - 1,00mm

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark