

Skewed cross



Available in heights (H):

- 50
- 75
- 100

Dimension							Thickness	Weight	Technical Info			Code
W (B)	01	03	11	15	40	41	[mm]	[Kg]	a	w (b)	R	
100	01	03	11	15	40	41	1,00	1,80	400	360	100	T1 131 1010
150	01	03	11	15	40	41	1,00	2,59	500	410	100	T1 131 1015
200	01	03	11	15	40	41	1,00	3,54	600	460	100	T1 131 1020
300	01	03	11	15	40	41	1,00	5,91	800	560	100	T1 131 1030
400	01	03	11	15	40	41	1,00	8,91	1000	660	100	T1 131 1040
500	01	03	11	15	40	41	1,00	12,54	1200	760	100	T1 131 1050
600	01	03	11	15	40	41	1,00	16,80	1400	860	100	T1 131 1060

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark