

Skewed cross



Available in heights (H):

- 50
- 75
- 100

Dimension							Thickness	Weight	Technical Info			Code
									a	w (b)	R	
W (B)	01	03	11	15	40	41	[mm]	[Kg]	a	w (b)	R	
75	01	03	11	15	40	41	1,00	1,42	375	335	100	T1 131 0707
100	01	03	11	15	40	41	1,00	1,76	425	360	100	T1 131 0710
150	01	03	11	15	40	41	1,00	2,57	525	410	100	T1 131 0715
200	01	03	11	15	40	41	1,00	3,52	625	460	100	T1 131 0720
300	01	03	11	15	40	41	1,00	5,91	825	560	100	T1 131 0730
400	01	03	11	15	40	41	1,00	8,94	1025	660	100	T1 131 0740
500	01	03	11	15	40	41	1,00	12,58	1225	760	100	T1 131 0750
600	01	03	11	15	40	41	1,00	16,86	1425	860	100	T1 131 0760

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark