



Curva Cóncava 90° sin Tapa



Disponible en alturas (H):

50

75

100

Dimensiones							Peso	Datos Técnicos	Código
B							[Kg]	a	R
50	01	03	11	15	40	41	0,39	180	100
100	01	03	11	15	40	41	0,50	180	100
150	01	03	11	15	40	41	0,62	180	100
200	01	03	11	15	40	41	0,73	180	100
300	01	03	11	15	40	41	0,96	180	100
400	01	03	11	15	40	41	1,19	180	100
500	01	03	11	15	40	41	1,42	180	100
600	01	03	11	15	40	41	1,65	180	100

Espesor

Componente - 1,00mm

Certificaciones



E471266



Lista de Revestimientos

Galvanizado en caliente Sendzimir - UNI EN 10346

Galvanizado por inmersión en caliente - UNI EN ISO 1461

Gris RAL 7032 - ISO9227-ISO6270-ISO2810

Azul RAL 5015 - ISO9227-ISO6270-ISO2810

Acero Inoxidable AISI 304 - UNI EN 10088

Acero Inoxidable AISI 316L - UNI EN 10088

Sistema de certificación

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Atención: para ZT y ZM material vendido / montados en Estados Unidos y Canadá, por favor, requieren marca de UL