



Passerella con asolatura sfalsata



Disponibile nelle altezze (H):

15

18

Dimensione				Spessore		Spessore (18-42)		Peso (01)	Peso (42)	Lunghezza	Codice	
B						[mm]	[mm]	[Kg/m]	[Kg/m]	[mm]		
50	01	03	17	18	41	42	1,50	2,00	0,81	0,36	2000	NR 002 0105
75	01	03	17	18	41	42	1,50	2,00	1,06	0,48	2000	NR 002 0107
100	01	03	17	18	41	42	1,50	2,00	1,32	0,59	2000	NR 002 0110
125	01	03	17	18	41	42	1,50	2,00	1,57	0,71	2000	NR 002 0112
150	01	03	17	18	41	42	1,50	2,00	1,83	0,82	2000	NR 002 0115
200	01	03	17	18	41	42	1,50	2,00	2,34	1,06	2000	NR 002 0120
250	01	03	17	18	41	42	1,50	2,00	2,85	1,29	2000	NR 002 0125
300	01	03	17	18	41	42	1,50	2,00	3,36	1,52	2000	NR 002 0130
400	01	03	17	18	41	42	1,50	2,00	4,38	1,98	2000	NR 002 0140

Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Zincatura send.+ Bianco Ral 9010

Alluminio + Bianco Ral 9010

Inox AISI 316L - UNI EN 10088

ENAW 1050H24 - Alluminio