


Raccordo a 4 vie con Coperchio



Disponibile nelle altezze (H):

50

75

100

Dimensione		Peso	Dati Tecnici	Codice
B		[Kg]	a b R	
100	01 03 11 15	2,10	400 360 100	T0 131 1010
150	01 03 11 15	3,18	500 410 100	T0 131 1015
200	01 03 11 15	4,50	600 460 100	T0 131 1020
300	01 03 11 15	7,87	800 560 100	T0 131 1030
400	01 03 11 15	12,23	1000 660 100	T0 131 1040
500	01 03 11 15	17,57	1200 760 100	T0 131 1050
600	01 03 11 15	23,90	1400 860 100	T0 131 1060

Spessori

T1 131 - Componente - 1,00mm

T1 132 - Coperchio - 0,80mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL