


Raccordo a 4 vie con Coperchio



Disponibile nelle altezze (H):

50

75

100

Dimensione		Peso	Dati Tecnici	Codice
B		[Kg]	a b R	
75	01 03 11 15	1,64	375 335 100	T0 131 0707
100	01 03 11 15	2,09	425 360 100	T0 131 0710
150	01 03 11 15	3,19	525 410 100	T0 131 0715
200	01 03 11 15	4,54	625 460 100	T0 131 0720
300	01 03 11 15	7,96	825 560 100	T0 131 0730
400	01 03 11 15	12,37	1025 660 100	T0 131 0740
500	01 03 11 15	16,17	1225 760 100	T0 131 0750
600	01 03 11 15	24,13	1425 860 100	T0 131 0760

Spessori

T1 131 - Componente - 1,00mm

T1 132 - Coperchio - 0,80mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL