


Chiusura di estremità



Disponibile nelle altezze (H):

50

75

100

Dimensione						Spessore	Peso	Dati Tecnici		Codice
B						[mm]	[Kg]	a	b	
50	01	03	11	15	40	1,00	0,03	51	53	T0 250 0505
100	01	03	11	15	40	1,00	0,05	51	103	T0 250 0510
150	01	03	11	15	40	1,00	0,08	51	153	T0 250 0515
200	01	03	11	15	40	1,00	0,10	51	203	T0 250 0520
300	01	03	11	15	40	1,00	0,15	51	303	T0 250 0530
400	01	03	11	15	40	1,00	0,19	51	403	T0 250 0540
500	01	03	11	15	40	1,00	0,24	51	503	T0 250 0550
600	01	03	11	15	40	1,00	0,29	51	603	T0 250 0560

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Sistema Certificato

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
 Attenzione: per materiale Serie ZT e ZM
 venduto/installato in USA e Canada, richiedere la
 marcatura UL

Chiusura di estremità

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni giunto	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni giunto	

Non compresi

