


Flangia per attacco a quadro



Disponibile nelle altezze (H):

50

75

100

Dimensione						Spessore	Peso	Dati Tecnici				Codice
B						[mm]	[Kg]	a	b	c	d	
100	01	03	11	15	40	1,50	0,21	150	150	125	125	T0 260 1010
150	01	03	11	15	40	1,50	0,25	150	200	175	125	T0 260 1015
200	01	03	11	15	40	1,50	0,29	150	250	225	125	T0 260 1020
300	01	03	11	15	40	1,50	0,36	150	350	325	125	T0 260 1030
400	01	03	11	15	40	1,50	0,44	150	450	425	125	T0 260 1040
500	01	03	11	15	40	1,50	0,52	150	550	525	125	T0 260 1050
600	01	03	11	15	40	1,50	0,59	150	650	625	125	T0 260 1060

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Sistema Certificato

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
 Attenzione: per materiale Serie ZT e ZM
 venduto/installato in USA e Canada, richiedere la
 marcatura UL

Flangia per attacco a quadro

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni flangia	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni flangia	

Non compresi

