


Flangia per attacco a quadro



Disponibile nelle altezze (H):

50

75

100

Dimensione	Spessore	Peso	Dati Tecnici				Codice
B	[mm]	[Kg]	a	b	c	d	
50	01 03 11 15 40	1,50	0,11	100	100	75	75 T0 260 0505
100	01 03 11 15 40	1,50	0,15	100	150	125	75 T0 260 0510
150	01 03 11 15 40	1,50	0,19	100	200	175	75 T0 260 0515
200	01 03 11 15 40	1,50	0,22	100	250	225	75 T0 260 0520
300	01 03 11 15 40	1,50	0,30	100	350	325	75 T0 260 0530
400	01 03 11 15 40	1,50	0,38	100	450	425	75 T0 260 0540
500	01 03 11 15 40	1,50	0,45	100	550	525	75 T0 260 0550
600	01 03 11 15 40	1,50	0,53	100	650	625	75 T0 260 0560

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
Attenzione: per materiale Serie ZT e ZM
venduto/installato in USA e Canada, richiedere la
marcatatura UL

Flangia per attacco a quadro

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni flangia	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni flangia	

Non compresi

