


Flangia per attacco a quadro



Disponibile nelle altezze (H):

50

75

100

Dimensione	Spessore	Peso	Dati Tecnici				Codice
B	[mm]	[Kg]	a	b	c	d	
75	01 03 11 15 40	1,50	0,16	125	125	100	100 T0 260 0707
100	01 03 11 15 40	1,50	0,18	125	150	125	100 T0 260 0710
150	01 03 11 15 40	1,50	0,22	125	200	175	100 T0 260 0715
200	01 03 11 15 40	1,50	0,25	125	250	225	100 T0 260 0720
300	01 03 11 15 40	1,50	0,33	125	350	325	100 T0 260 0730
400	01 03 11 15 40	1,50	0,41	125	450	425	100 T0 260 0740
500	01 03 11 15 40	1,50	0,48	125	550	525	100 T0 260 0750
600	01 03 11 15 40	1,50	0,56	125	650	625	100 T0 260 0760

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL

Flangia per attacco a quadro

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni flangia	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni flangia	

Non compresi

