


Flangia di riduzione per attacco a quadro



Disponibile nelle altezze (H):

50

75

100

Dimensione						Spessore	Peso	Dati Tecnici				Codice
B						[mm]	[Kg]	a	b	c	d	
50	01	03	11	15	40	1,50	0,07	75	100	75	50	T0 261 0505
100	01	03	11	15	40	1,50	0,09	75	150	125	50	T0 261 0510
150	01	03	11	15	40	1,50	0,11	75	200	175	50	T0 261 0515
200	01	03	11	15	40	1,50	0,13	75	250	225	50	T0 261 0520
300	01	03	11	15	40	1,50	0,17	75	350	325	50	T0 261 0530
400	01	03	11	15	40	1,50	0,21	75	450	425	50	T0 261 0540
500	01	03	11	15	40	1,50	0,25	75	550	525	50	T0 261 0550
600	01	03	11	15	40	1,50	0,29	75	650	625	50	T0 261 0560

Certificazioni



E471266



Legenda Trattamenti

 Zincato Sendzimir - UNI EN 10346

 Zincatura a caldo per immersione - UNI EN ISO 1461

 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

 Blu RAL 5015 - ISO9227-ISO6270-ISO2810

 Inox AISI 304 - UNI EN 10088

Sistema Certificato

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
- Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL

Flangia di riduzione per attacco a quadro

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni flangia	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni flangia	

Non compresi

