


Flangia di riduzione per attacco a quadro



Disponibile nelle altezze (H):

50

75

100

Dimensione						Spessore	Peso	Dati Tecnici				Codice
B						[mm]	[Kg]	a	b	c	d	
75	01	03	11	15	40	1,50	0,11	100	125	100	75	T0 261 0707
100	01	03	11	15	40	1,50	0,12	100	150	125	75	T0 261 0710
150	01	03	11	15	40	1,50	0,14	100	200	175	75	T0 261 0715
200	01	03	11	15	40	1,50	0,16	100	250	225	75	T0 261 0720
300	01	03	11	15	40	1,50	0,20	100	350	325	75	T0 261 0730
400	01	03	11	15	40	1,50	0,24	100	450	425	75	T0 261 0740
500	01	03	11	15	40	1,50	0,28	100	550	525	75	T0 261 0750
600	01	03	11	15	40	1,50	0,32	100	650	625	75	T0 261 0760

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL

Flangia di riduzione per attacco a quadro

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni flangia	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni flangia	

Non compresi

