



Riduzione Sinistra senza Coperchio



Disponibile nelle altezze (H):

50

75

100

							Peso	Dati Tecnici	Riduzione da	Codice	
							[Kg]	L	B	B1	
01	03	11	15	40	41		0,46	220	150	100	T1 075 3433
01	03	11	15	40	41		0,55	220	200	150	T1 075 3534
01	03	11	15	40	41		0,68	220	300	200	T1 075 3635
01	03	11	15	40	41		0,85	220	400	300	T1 075 3736
01	03	11	15	40	41		1,02	220	500	400	T1 075 3837
01	03	11	15	40	41		1,20	220	600	500	T1 075 3938

Spessori

Componente - 1,00mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attenzione: per materiale Serie ZT e ZM
venduto/installato in USA e Canada, richiedere la
marcatura UL