


Raccordo 4 vie con variazione di piano



Disponibile nelle altezze (H):

50

75

100

Dimensione							Spessore	Peso	Dati Tecnici			Codice
B							[mm]	[Kg]	a	b	R	
50	01	03	11	15	40	41	1,00	1,04	350	310	100	T1 131 0505
100	01	03	11	15	40	41	1,00	1,70	450	360	100	T1 131 0510
150	01	03	11	15	40	41	1,00	2,51	550	410	100	T1 131 0515
200	01	03	11	15	40	41	1,00	3,48	650	460	100	T1 131 0520
300	01	03	11	15	40	41	1,00	5,89	850	560	100	T1 131 0530
400	01	03	11	15	40	41	1,00	8,93	1050	660	100	T1 131 0540
500	01	03	11	15	40	41	1,00	12,60	1250	760	100	T1 131 0550
600	01	03	11	15	40	41	1,00	16,89	1450	860	100	T1 131 0560

Certificazioni



E471266



Legenda Trattamenti

 Zincato Sendzimir - UNI EN 10346

 Zincatura a caldo per immersione - UNI EN ISO 1461

 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

 Blu RAL 5015 - ISO9227-ISO6270-ISO2810

 Inox AISI 304 - UNI EN 10088

 Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
 Attenzione: per materiale Serie ZT e ZM
 venduto/installato in USA e Canada, richiedere la
 marcatura UL