


Raccordo 4 vie con variazione di piano



Disponibile nelle altezze (H):

50

75

100

Dimensione							Spessore	Peso	Dati Tecnici			Codice
B							[mm]	[Kg]	a	b	R	
75	01	03	11	15	40	41	1,00	1,42	375	335	100	T1 131 0707
100	01	03	11	15	40	41	1,00	1,76	425	360	100	T1 131 0710
150	01	03	11	15	40	41	1,00	2,57	525	410	100	T1 131 0715
200	01	03	11	15	40	41	1,00	3,52	625	460	100	T1 131 0720
300	01	03	11	15	40	41	1,00	5,91	825	560	100	T1 131 0730
400	01	03	11	15	40	41	1,00	8,94	1025	660	100	T1 131 0740
500	01	03	11	15	40	41	1,00	12,58	1225	760	100	T1 131 0750
600	01	03	11	15	40	41	1,00	16,86	1425	860	100	T1 131 0760

Certificazioni



E471266



Legenda Trattamenti

 Zincato Sendzimir - UNI EN 10346

 Zincatura a caldo per immersione - UNI EN ISO 1461

 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

 Blu RAL 5015 - ISO9227-ISO6270-ISO2810

 Inox AISI 304 - UNI EN 10088

 Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
 Attenzione: per materiale Serie ZT e ZM
 venduto/installato in USA e Canada, richiedere la
 marcatura UL